



APMED'12 PROGRAM

აჯარის აკადემიუმის რეაქცია
აათავისტებულისა და საზოგადო სამინისტრო



BATUMI SHOTA RUSTAVELI STATE UNIVERSITY

12th Japanese-Mediterranean Workshop Applied Electromagnetic Engineering for Magnetic, Superconducting, Multifunctional and Nanomaterials



BOOK OF ABSTRACTS

17-20 JULY, 2023

PROGRAM

³ *Laboratory of Energy and Industrial Economics (LIEE), National Technical University of Athens, Greece*

14:00 – 14:20 **D2 (107): Health Hazards and Pollution Risk from Large Battery Energy Storage Systems**
 J.Ramsden
*Faculty of Medicine and Health Sciences, The University of Buckingham, England,
jeremy.ramsden@buckingham.ac.uk*

14:20 – 14:40 **D3 (109): Analysis of Possibilities the Current Situation for Using and Accumulating Green Energies in Georgia**
 R.Turmanidze¹, N. Gomidze^{2*}, G.Popkhadze¹, L.Gomidze³
¹*Georgian Technical University, Tbilisi, Georgia, inform@gtu.ge*
²*Batum Shota Rustaveli State University, Georgia, gomidze@bsu.edu.ge*
³*Department of Exact and Natural Sciences, Tbilisi State University, 0179, Tbilisi, Georgia*

14:40 – 15:00 **D4 (106): Discovering the Cause of Aerotoxic Syndrome: A Causal Calculus Approach**
 J. J. Ramsden
*Faculty of Medicine and Health Sciences, The University of Buckingham, England
jeremy.ramsden@buckingham.ac.uk*

15:00 – 15:20 **D5 (111): An Overview of Life Cycle Assessment Criteria for Transportation Decision-Making**
 N.T. Athanassoulis ^{*}, A.Tsakanikas
*Laboratory of Industrial & Energy Economics National Technical University of Athens,
¹nathanas@ce ²atsaka@central.ntua.gr*

15:20 – 15:50 Coffee Break

15:50 – 18:30 Oral Session E: Composite, Ceramic and Magnetic Nanomaterials
 Chair: A. Dwivedi

15:50 – 16:20 **Keynote Presentation E1 (17): Effect of Nanoadditives on the Properties of Partially Stabilized Zirconia**
 A.Mamalis^{1,a}, E.Hevorkian^{2,b}, V.Nerubatskyi^{3,c}, M. Rucki^{4,d} Z. Krzysiak², O.Morozova^{3,c}
¹*Project Center for Nanotechnology and Advanced Engineering, Athens, Greece,
agmamalis@yahoo.com*
²*University of Life Sciences in Lublin, 13 Akademicka, Lublin 20-950, Poland, ^bcernetu@mail.com*
³*Ukrainian State University of Railway Transport, Kharkiv, Ukraine, ^cNVP9@i.ua,
oksanabakan2012@gmail.com*
⁴*Kazimierz Pulaski University of Technology and Humanities in Radom, Poland,
^dm.rucki@uthrad.pl*

16:20 – 16:40 **E2 (114): Effect of CrB2 Reinforcement on the Mechanical Properties of Ceramic Matrix Composites (CMCs) and Metal Matrix Composites (MMCs)**
 M. Rucki^{1,a}, E.Hevorkyan^{2,b}, V.Mechnik^{3,c}, B. Ratov^{4,d}, S. Muratova^{5,e}
¹*Kazimierz Pulaski University of Technology and Humanities in Radom, Radom, Poland,
m.rucki@uthrad.pl*
²*University of Life Sciences in Lublin, Lublin, Poland, ^bedsgev@gmail.com*
³*Bakul Institute for Superhard Materials, National Academy of Sciences of Ukraine, Kyiv, Ukraine, ^cvlad.me4nik@ukr.net*
⁴*Satpayev University, Almaty, Kazakhstan, ^db.ratov@satbayev.university*
⁵*Caspian University, Almaty, Kazakhstan, ^esamal.muratova@cu.edu.kz*

EFFECT OF NANOADDITIVES ON THE PROPERTIES OF PARTIALLY STABILIZED ZIRCONIA

A.G. Mamalis^{1,a}, E.S. Hevorkian^{2,b}, V.P. Nerubatskyi^{3,c}, M. Rucki^{4,d} Z. Krzysiak², O.M. Morozova^{3,e}

¹*Project Center for Nanotechnology and Advanced Engineering, Athens, Greece,*

^aagmamalis@yahoo.com

²*University of Life Sciences in Lublin, 13 Akademicka, Lublin 20-950, Poland,* ^bcermet-u@mail.com

³*Ukrainian State University of Railway Transport, Kharkiv, Ukraine,* ^cnerubatskyi@kart.edu.ua,

^eoksanabakan2012@gmail.com

⁴*Kazimierz Pulaski University of Technology and Humanities in Radom, Poland,* ^dm.rucki@uthrad.pl

The structure determining factor for of nanocrystalline materials is the extremely small grain size, the resulting large area of the boundaries and correspondingly the length of their joints in the volume unit, the difficulty or suppression of dislocation mechanisms of plastic deformation at grain sizes below a certain limiting value and the nonequilibrium state of the grain boundaries [1]. The developed surface of isolated nanoparticles initiates dimensional effects of thermodynamic quantities. Due to the existence of a significant number of atoms near the surface of the nanomaterial, as well as the lattice dynamics, which undergoes substantial changes due to a number of features of the nanostate, such substance characteristics as values of heat capacity [2], thermal conductivity [3, 4], melting temperature, Debye temperature depend.

In the case of a non-electrically conductive pure zirconia sample, there is no joule heating during current flow through the powder mixture, i.e. the initial heating of the sample is done by current flow through the graphite mold, in contrast to the case of tungsten carbide samples, where joule heating starts immediately, i.e. the structure formation occurs mainly already during heating to the dwell temperature. The high heating rate minimizes the influence of diffusion processes on the particle surfaces, which do not contribute to densification, and the samples reach high temperatures faster while retaining the ability to sinter. That is, rapid heating accelerates densification due to earlier activation of dislocation creep mechanisms and due to reduction of the low-temperature stage sintering, when surface diffusion dominates.

Various nanoadditives to zirconium dioxide affect primarily the hardness and strength of the composite as a whole. They increase these values in different ways, depending on their content and sintering regimes. Hot pressing by electrosintering, significantly activates the compaction process, contributes to the formation of a fine microstructure. The mechanism of the sintering process occurs differently, depending on the ability to conduct electric current, strengthening additives. creation of a functional gradient material, the top layer of which will be ZrO₂-Al₂O₃, the middle ZrO₂-SiC, the bottom layer ZrO₂-WC. The material can have a polyfunctional application, one of the most promising applications would be the production of laminated plates for cutting tools. The question of choosing the optimal composition for each layer will be determined by the working conditions of this material.

Reference:

- [1] Sirota V., Ivanisenko V., Pavlenko I., Hevorkyan E., Chishkala V., Kovaleva M..Synthesis and consolidation of (Zr0.94Y0.06)O1.88 nanopowders. Ceram International,2015;41:5263–9.
- [2] Hevorkyan E., Lavrynenko S., Rucki M., Siemiatkowski Z., Kisliitsa M. Preparation of nanostructured materials by electrical sintering 2017;11–15:663–6.
- [3] Chena X., Liub L., Donga Y. Preparation of nano-sized Bi₂Te₃ thermoelectric material powders by cryogenic grinding. Progress in Natural Science. Materials International. 2012, 22, 3, 201–206.
- [4] Vanleeuwen B.K., Darling K.A., Koch C.C., Scattergood R.O. Novel technique for the synthesis of ultra-fine porosity metal foam via the inclusion of condensed argon through cryogenic mechanical alloying. Materials science and Engineering: A. Structural Materials. 2011, 528, 4–5, 2192–2195.